

Carlon[®]

Liquidtight Flexible Non-Metallic Conduit & Fittings T&B Catalog Number:

15005-100

UPC Number: 03448123305

Status: Active

Description:

1/2 inch gray liquidtight flexible non-metallic conduit, 100 ft.coil.

1/2 inch gray liquidtight flexible non-metallic conduit, 100 ft.coil.	
Features	
	Non-conductive and non-corrosive.
	Lightweight for easy handling, transportation and in-
	stallation.
	Crush, abrasion and strain resistant.
	Provides superior wire protection
	Smooth interior ideal for pulling cable, no jagged edges.
	Maintains internal I.D. even in tight radius bends.
	Resistant to oil, acid, ozone, and alkaline.
	UL listed for outdoor use and sunlight resistant.
	UL listed for use as indicated in Article 356.2 of the NEC® and Section 12-1300 of the Canadian Electrical Code, Part 1.
	Suitable for use at conduit temperatures of 80° C dry, 60° C wet and 60° C oil resistant as required by Section 15-6 of ANSI/NFPA 79 and UL 1660.
	Sequentially market footage
General	
Material	Non-Metallic
Color	Gray
Dimension Information	
Average O.D. (inches)	0.830
Average I.D. (inches)	0.627
Nominal Size (inches)	1/2
Coil Length (feet)	100
Packaging	
T&B Order Multiple	100
Package in Units	100
T&B Sold in UOM	Feet
T&B Weight Per UOM	0.15 lbs. Each
Application Support	
T&B Sales Drawings	wsd-ac03996
Product Overview-Carflex Liquidtight Flex	r-Available on Website
ible Tubing	
Notes	
*Note	Available in black and gray.
**Note	Customer cut lengths available.
Certifications	
RoHS Compliance	Yes



Certifications



File Nbr: E 79553

For further technical assistance, please contact us...

Thomas & Betts - USA

8155 T&B Blvd.

Memphis, TN 38125

www.tnb.com

T&B Technical Support

MS 3B-50

8155 T&B Blvd.

Memphis, TN 38125

Memphis, TN 38125

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Email:techsupport@tnb.com