



# Carlton®

## Liquidtight Flexible Non-Metallic Conduit & Fittings

**T&B Catalog Number:**

**UPC Number:** 15007-100  
**Status:** 03448123315  
**Description:** Active

3/4 inch gray liquidtight flexible non-metallic conduit, 100 ft. coil.

### Features

Non-conductive and non-corrosive.
Lightweight for easy handling, transportation and installation.
Crush, abrasion and strain resistant.
Provides superior wire protection
Smooth interior ideal for pulling cable, no jagged edges.
Maintains internal I.D. even in tight radius bends.
Resistant to oil, acid, ozone, and alkaline.
UL listed for outdoor use and sunlight resistant.
UL listed for use as indicated in Article 356.2 of the NEC® and Section 12-1300 of the Canadian Electrical Code, Part 1.
Suitable for use at conduit temperatures of 80&deg; C dry, 60&deg; C wet and 60&deg; C oil resistant as required by Section 15-6 of ANSI/NFPA 79 and UL 1660.
Sequentially market footage

### General

Material	Non-Metallic
Color	Gray

### Dimension Information

Average O.D. (inches)	1.040
Average I.D. (inches)	0.825
Nominal Size (inches)	3/4
Coil Length (feet)	100

### Packaging

T&B Order Multiple	100
Package in Units	100
T&B Sold in UOM	Feet
T&B Weight Per UOM	0.18 lbs. Each

### Application Support

T&B Sales Drawings	wsd-ac04219
Product Overview-Carflex Liquidtight Flex-Available on Website	
ible Tubing	

### Notes

*Note	Available in black and gray.
**Note	Customer cut lengths available.

### Certifications

RoHS Compliance	Yes
-----------------	-----

**Certifications**



File Nbr:  
E 79553

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)