

## KS23 Specifications

<b>Dimensional</b>	
Width (in)	0.62
Size (Hex) or Size (Bolt)	5/8
Cross Flats	0.82
Size (Hex) or Size (Bolt) - in	0.625
B Length (in)	0.72
B Length (Fraction)	18/25
<b>Other Features</b>	
UPC	78181001275
<b>Conductors</b>	
Copper Tap (Range)	14 AWG - 2 AWG
Copper Weld Solid Run Size (Range)	N/A
Copper Stranded Run (Range)	6 AWG - 2 AWG
Copper Weld Stranded Tap Size (Range)	5 D AWG - 3 A AWG
Copper Solid Tap (Range)	N/A
Copper Weld Solid Tap Size (Range)	7 AWG - 4 AWG
Copper Solid Run Size (Range)	N/A
Copper Weld Stranded Run Size (Range)	5 D AWG - 3 A AWG
<b>Approvals / Certifications</b>	
Rated for Direct Burial	Yes
UL Listed	Yes
CSA Certified	Yes
ROHS Compatible	Compliant
UL Recognized	No
Industry Standards	UL468A-468B
<b>Physical</b>	
Installation Torque	275
Type of Plating	Unplated
Connector Type	Split Bolt
Plated (Yes or No)	No
Product Material	Copper