# **Aervoe Construction Marking Paint - Aerosol**



The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900. 1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following Aervoe aerosol products.

**PRODUCT NAME:** Construction Marking Paint

Fluorescent Colors		Non-Fluorescent Colors		
246 Red	249 Pink	251 Black	256 Red	
247 Orange	250 Blue	252 Yellow	257 Orange	
248 Green	253 Yellow	254 Blue	258 Hi Vis Yellow	
	283 Red-Orange	255 White	259 Green	
			260 Purple	

### **SECTION I - MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: Aervoe Industries, Inc.

**INFORMATION PHONE:** 775-783-3100 DATE REVISED: August 12, 2009

ADDRESS: 1100 Mark Circle, Gardnerville, NV 89410

**EMERGENCY PHONE:** 1-800-424-9300 **REASON REVISED:** Ingredient Change

## SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Hydrocarbon Propellan (CAS 68476-86-8)	it 10 - 30	1000 ppm	1000 ppm	N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-89-8) 7 - 13		N / AV	300 ppm	N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-88-7) 1 - 5		100 ppm	100 ppm	N / AV	N / AV
Non-Fluorescent Colo	ors Also Contain	=			
*Hexane (CAS 110-54-3)	7 - 13	500 ppm	50 ppm (skin)	2870 mg / kg (Rat-Oral)	N / AV
Acetone (CAS 67-64-1)	1 - 5	1000 ppm	500 ppm	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat-Inha)
Fluorescent Colors A	Iso Contain:			00 000 04 000	
Propylene Glycol (CAS 57-55-6)	1 - 5	N / AV	N / AV	20,000-34,000 mg / kg (Rat-Oral) N / AV > 10,000 mg / kg (Rabbit-Skin)	

<sup>\*</sup>Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N / AP = Not Applicable N / AV = Not Available

Construction Marking Paint August 12, 2009

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT: N / AP** SPECIFIC GRAVITY (H20=1): 0.9 VAPOR DENSITY: Heavier than air **SOLUBILITY IN WATER: Partial** 

**EVAPORATION RATE:** Faster than n-Butyl Acetate APPEARANCE AND ODOR: Opaque liquid with hydrocarbon odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS - LEL: 0.9% UEL: 13.0% **FLASH POINT:** < 0° F (-18° C) METHOD USED: Estimated

**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up.

Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Treat as cylinders of compressed gas. Closed containers may rupture due to

pressure build up from extreme temperature.

FLAMMABILITY: Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.

SENSITIVITY TO IMPACT: Do not puncture SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

**SECTION V - REACTIVITY DATA** 

STABILITY: Stable CONDITIONS TO AVOID: Open flames, sparks, electrical arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

#### SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches, Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

SKIN CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.

EYE CONTACT: Painful with slight to moderate irritation.

INGESTION: May be harmful or fatal if swallowed

EFFECTS OF CHRONIC OVEREXPOSURE: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and

nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.

TERATOGENICITY: Not established MUTAGENICITY: Not established

MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.

SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.

INGESTION - Do not induce vomiting. Contact physician or poison control center immediately.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.

OTHER PRECAUTIONS: Avoid contact with eyes and skin. Do not breathe vapors, take internally or smoke while using this product.

#### **SECTION VIII - CONTROL MEASURES**

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.

For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.

VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II.

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not established.

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

#### **SECTION IX - DISCLAIMER**

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.