8" PRO SERIES CHANNEL™ DRAINS

Patented

				*Produce	ed under lice	ense of First Plast S.R.L Italy
Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
836	8" x 20" Pedestrian Traffic Channel Grate	Light Gray	1	1.55	25IN	NDS #836, 8" Wide UV protected high impact
I 3/4"	Requires #829 screws. 4 screws per	r grate				Polyolefin pedestrian traffic channel grate.
	* Ozo obiowa: 4 obiowa pol	grato.				Open surface area 11.70 square inches per
19 5 %	K					foot. 15.33 GPM per foot.
1/4" Grate Opening	(See pg. 47) ADA Complia		ant			
			Pkg.	Wt. Ea.	Product	
Part No.	Description	Color	Qty.	(lbs.)	Class	Specifications
837	8" x 20" Light Traffic Channel Grate	Light Gray	1	3.00	25IN	NDS #837, 8" Wide UV protected high impact
I 3/4"	Requires #829 screws. 4 screws per grate.					Polyolefin light traffic channel grate. Open
5/1						surface area 26.94 square inches per foot.
19 5 18	(See pg. 47)					35.29 GPM per foot.
%" x 2" Grate Opening						
Part No.	Docarintion	Color	Pkg.	Wt. Ea. (lbs.)	Product Class	Specifications
838	Description 8" x 20" Load Star Heavy	Light Gray	Qty.	4.00	25IN	NDS #838, 8" Wide UV
1 ¾"	Traffic Channel Grate*	Light Gray	ı	4.00	25111	protected high impact glass reinforced nylon
1/4	Requires #829 screws. 4 screws per grate.					heavy traffic channel grate. Open surface area 30.85
5/1						square inches per foot. 40.41 GPM per foot.
19	(See pg. 47)					40.41 GI W per 100t.
½" x 5 ¾" Grate Opening	ADA Compliant					
B . N			Pkg.	Wt. Ea.	Product	
Part No. 888	Description 8"x20" Cast Iron Channel Grate	Color Black	Qty.	(lbs.)	Class	Specifications
		1	14.00	25IN	NDS #888, 8" Wide Heavy Duty Cast Iron Heavy	
± ¾"	#829 screws may be used. 4 screws per grate.					Traffic Channel Grate. Open surface area 41.25 square inches per foot. 54.04 GPM per foot.
195%	(See pg. 47)					
%" x 6 %" Grate Opening						
3 /3 C.						


MODULAR CHANNEL DRAINS

Patented

*Produced under license of First Plast S.R.L.- Italy

	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
19 7/8"	↓ ├──	ications. Grate sho					NDS #830, 8" Wide Shallow Profile high impact PVC channel drain with mechanical interlocking joints and UV inhibitors.

	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
2" 14 1/4"	831	8" Shallow Profile End Cap/ 3" S&D SPT Knock Out End Outlet*	Light Gray	1	0.40	25IN	NDS #831, 8" Wide Shallow Profile high impact PVC End Cap/End Outlet.
	Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
7 7/8	832	8" Shallow Profile 3" S&D	Light Gray	1	1.00	25IN	NDS #832, 8" Wide




Shallow Profile high impact PVC Bottom/Side Outlet.

Pkg. Wt. Ea.

Product

Bottom outlet fits 4" S&D pipe, 3" S&D fittings

Part No.	Description		Color	Qty.	(lbs.)	Class	Specifications
833	8" x 20" Deep Profile Channel Drain		Light Gray	1	3.00	25IN	NDS #833, 8" Wide Deep Profile high impact PVC channel drain with
1	Grate should be recessed 1/8" below finish grade in non traffic applications. Grate should be recessed 1/4" in traffic applications.						mechanical interlocking joints and UV inhibitors.



Part No.	Description	Color	Pkg. Qty.	Wt. Ea. (lbs.)	Product Class	Specifications
834	8" Deep Profile End Cap/ 3"&4" S&D SPT Knock Out	Light Gray	10	1.20	25IN	NDS #834, 8" Wide Deep Profile high impact PVC End Cap/End Outlet

