

**AA Thread Seal Tape, Inc.**

1275 Kyle Court

Wauconda, IL 60084

**Phone:** 847.526.2120 • **Fax:**847.526.2209**Email:** sales@aathread.com • **Website:**www.aathread.com**Item # 40101C, Standard Density PTFE Thread Seal Tapes - Made in China****Standard Density PTFE Thread Seal Tapes - Made in China****WHITE PTFE THREAD SEAL TAPE**

For all industrial applications. Made from 100% virgin PTFE. No pigments, no additives. May be used on all applications including water, oil, chemical, medical, and food processing where non-contamination standards are high. Exceeds MIL Spec T-27730A. Temperature range of -450°F to +550°F. Available in a variety of sizes and densities.

· [SPECIFICATIONS](#) · [CASE DIMENSIONS](#)

**SPECIFICATIONS**

Size	3/4" x 520"
Density	0.4
Country of Origin	China
Chemical Properties	100% Polytetrafluoroethylene
Thickness	0.0035" (+/- 0.0005")
Elongation	Min. 50%
Width	3/4" (+/- 0.02")
Length	520 in
Pressure Rating	10000 psi
Government Standard	Meets MIL Spec T-27730A
Quantity/Case	350
Inner Boxes	5/70
Weight/Case	22 Lbs
Incompatibility	Avoid using on Molten Alkali, certain Halogen products and Fluorine at high temperatures and pressures.
Temperature	When heated over 500°F (260°C), it will thermally degrade and decompose producing toxic fumes.

Usage	To be used on all types of threaded fittings for passage of water, potable and non-potable, most chemicals, oxygen, gas, hydraulic and high pressure lines.
-------	---

---

**CASE DIMENSIONS**

Length	23 in
Width	11 1/2 in
Height	8 in

---